

# CreteCare Floor Polish Datasheet

October 2017

Page 1 of 2

**CreteCare Floor Polish** is an easy to apply, high gloss, hardwearing, protective polish for cement and concrete floors, terra cotta tiles, slate, terrazzo, sandstone, limestone and vinyl surfaces. **CreteCare Floor Polish** delivers excellent black heel mark, slip, detergent and wear resistance with high lay down gloss retention. This is a state-of-the art low-ammoniated product.

## Technical Data

Type	Acrylate polymer emulsion
Colour	Opaque in wet stage and dries clear
Working time after mixing	N/A
Application temperature (ambient)	5°C to 30°C
Substrate temperature	5°C to 30°C
UV resistance	Non-yellowing internal application
Abrasive resistance	Good wearing coat to protect sealers
Density	1kg/lt
Protection during application	Don't apply to hot surfaces, block sun when applying.
Safety	See MSDS

## Purpose

**CreteCare Floor Polish** is suitable for high traffic areas and promotes abrasion, scuff and slip resistance. It can also be used on some wall surfaces such as Cemcrete's SatinCrete and CreteCote skim plaster for additional affects.

## Applications

Specifically designed to protect sealed Cemcrete floor products, can also be used on vinyl, stone, tile, wood floors. Suitable for interior only.

## Colours

Dries clear and is non-yellowing.

## Site Work

## Storage

Store out of direct sunlight and avoid extreme temperatures. Use within 1 year after date of invoice.

## Suitable Surfaces

**CreteCare Floor Polish** is suitable for new, sealed concrete floors, existing sealed floors from which all previous polish applications have been removed.

## Surface Preparation

### New Floors

Ensure sealed surface is clean, dry and clear from dirt and grease.

### Existing Floors

For best results remove dirt, grease, and old sealers or polish build up with Cemcrete's CreteCare Floor Stripper according to its datasheet. Rinse the floor thoroughly with clean water and allow to dry completely. It is important that all previous polish is completely removed.

Cemcrete provides a comprehensive technical service based on over 3 decades of experience in the field of surface applications and cement technology. Cemcrete believes, to the best of its knowledge, that the information contained herein is true and accurate at the date of issuance and is subject to change without prior notice. For further clarification of these instructions, contact Cemcrete.

# CreteCare Floor Polish Datasheet

October 2017

Page 2 of 2

## Masking

---

For best results all windows, doors and adjacent surfaces should be masked using painters masking tape (blue) and brown paper. All masking material must be removed at the end of the day's work.

## Mixing

---

No mixing required - use as supplied.

## Preparation

---

Apply **CreteCare Polish** thinly and evenly in one direction preferably with a lamb's wool applicator. Make sure that no bubbles or streaks exist in the newly applied film. Do not rub. Allow this coat to dry for 30 minutes and apply second and third coats if required due to substrate porosity and sheen requirements. Allow for last coat to cure for at least 12 hours. Cured polish may be machine buffed if required to improve gloss.

## Coverage

---

Coverage is approximately 30-50m<sup>2</sup> per 1 litre, depending on surface porosity and method of application.

## Packaging

---

**CreteCare Floor Polish** is available in 5 litre plastic containers.

## Safety Precautions

---

Can cause burns and irritation to respiratory system. In case of contact with eyes, rinse immediately with water and seek medical advice. Wear suitable protective clothing and gloves.

## Manufacturer's Warranty

---

Cemcrete warrants that the products manufactured by it shall be free from material defects and will be consistent with its normal high quality. Should any of the products be proven defective, the liability to Cemcrete shall be limited to replacement of the product ex-factory. Cemcrete makes no warranty as to merchantability or fitness for a particular purpose and this warranty is in lieu of all other warranties expressed or implied. The user shall determine the suitability of the product for his intended use and assume all risks and liability in connection therewith.

Cemcrete provides a comprehensive technical service based on over 3 decades of experience in the field of surface applications and cement technology. Cemcrete believes, to the best of its knowledge, that the information contained herein is true and accurate at the date of issuance and is subject to change without prior notice. For further clarification of these instructions, contact Cemcrete.

---

### Johannesburg Head Office

8 Telford Street  
Industria  
011 474 2415

### Johannesburg Showroom

227 Jan Smuts Avenue  
Parktown North  
011 447 3149

### Centurion Showroom & Warehouse

15 Coachmen's Park  
26 Jakaranda Street, Centurion  
012 653 6808

### Cape Town Showroom & Warehouse

Eagle Park, cnr Bosmansdam &  
Omuramba Roads, Montague Gardens  
021 555 1034