

# CRETECOTE

Thin skim-on floor coating

---

A coloured, thin film cement based floor covering which is versatile and durable. It is a two coat system which produces a 1.6mm smooth decorative finish ideal for internal domestic renovations. Comes complete with powder and catalyst as a twin pack.

Creating distinctive cement finishes  
as *unique* as you are.

**ICEMCRETE**<sup>®</sup>

Manufacturers of Distinctive Decorative Coatings



*Did you know*

CreteCote is a micro coating and was created to provide the look and feel of concrete, but at a fraction of the cost and weight of real concrete.

CreteCote Sand Dollar

The colours depicted are a guide only and Cemcrete recommends choosing colours from an actual on-site sample. Different sealing methods might also affect the final colour.



Benefits

- Thin skim-on coating perfect for renovations
- Interior use only
- Application with a steel trowel
- Versatile application – can be used to coat counters & vanities
- Reaches a compressive strength of 35MPa after 28 days (this is solely dependent on the substrate)

Specifications

Suitable Surfaces	Wood or steel floated concrete floor slabs or screeds (interior only) New surfaces should be allowed to cure for at least 28 days Tiles - as long as the necessary preparation steps are followed to ensure adhesion. Refer to coating over tiles datasheet.
Finish	Smooth
Thickness	1.6mm (maximum 0.8mm per coat – 2 coat application)
Application	Sponge & trowel-on
Packaging	15kg twin-pack drum
Coverage	8-10m <sup>2</sup> per 15kg drum
Curing	The completed work should be allowed to air cure for 24 hours after application, before mist spraying the entire floor evenly at least twice during the day thereafter. Thereafter leave approximately 48 hours before sealing. The moisture in the floor must be less than 5% prior to sealing.
Colour/s	Available in 11 colours

Intended for use with

Concrete Floor Primer 5 & 20litre – 5m<sup>2</sup> per litre  
CreteSeal-Waterbased 1 & 5 litre – 8-10m<sup>2</sup> per litre per coat

Tools needed

Mechanical mixer  
Sponge  
Steel trowel  
Abranet sand paper

Supporting Cemcrete Products

CreteCare Mop & Shine  
CreteCare Polish  
CreteCare Floor Polish Stripper

CreteCote Colour Range




White



Sand Dollar




Grey



Dune



Coconut




Ivory



Mushroom



Tan



Brown Suede



Nickel Grey



Shale



CreteCote White

The colours depicted are a guide only and Cemcrete recommends choosing colours from an actual on-site sample. Different sealing methods might also affect the final colour.



CreteCote Nickel Grey



CreteCote Sand Dollar



CreteCote Nickel Grey coated vanity



CreteCote Nickel Grey



CreteCote Grey coated counters  
CreteCote White floor

The colours depicted are a guide only and Cemcrete recommends choosing colours from an actual on-site sample. Different sealing methods might also affect the final colour.

0860 CEMCRETE

info@cemcrete.co.za

www.cemcrete.co.za



blog.cemcrete.co.za

## HEAD OFFICE

---

### Showroom & Warehouse

8 Telford Street

Industria

(011) 474 2415

info@cemcrete.co.za

## GAUTENG

---

### Johannesburg Showroom

227 Jan Smuts Avenue

Parktown North

(011) 447 3149

jsa@cemcrete.co.za

### Centurion Showroom & Warehouse

15 Coachmen's Park

26 Jakaranda Street

Centurion

(012) 653 6808

pretoria@cemcrete.co.za

## CAPE TOWN

---

### Showroom & Warehouse

Unit 3 Eagle Park

cnr Bosmansdam & Omuramba Roads

Montague Gardens

(021) 555 1034

cape@cemcrete.co.za

We have distributors nationally, in most African countries and internationally. Contact us to locate your nearest stockist or contractor.

**CEMCRETE®**

Manufacturers of Distinctive Decorative Coatings



On the cover:  
CreteCote Grey

The colours depicted are a guide only and Cemcrete recommends choosing colours from an actual on-site sample. Different sealing methods might also affect the final colour.